ISSN:3030-332X
Impact factor: 9,493
International journal of scientific researchers

REDUCING VIBRATION IN GEAR HOBBING PROCESS

Abdufattokh Abdugofurov
Almalyk state technical institute
EMAIL: abdufattoh2521@gmail.com
TEL: +99893-121-25-21
Doi: https://doi.org/10.5281/zenodo.20133894

Abstract: These days modern technology is becoming more advanced, as a result of that mechanical engineering is becoming core ingredient of advancing machinery. This affects more positively to everyday life. For example: every aspect of life is covering technology agriculture, space or even medicine. We use automobiles in our everyday life to reach our destination as fast as possible. So, all machinery has gears to run wheels, as a result attending to producing gears is becoming important. During the working process machineries might have some vibration. As well as during the gear hobbing time we might see some level of vibration.

Vibration, particularly self-excited chatter, remains one of the most critical challenges in gear hobbing processes, significantly affecting machining accuracy, surface integrity, and tool life. This study investigates the underlying causes of vibration in gear hobbing, focusing on the dynamic interaction between cutting forces, tool geometry, machine tool rigidity, and workpiece stability. Based on this analysis, a novel approach for vibration suppression is proposed in the form of a hybrid smart-damped mandrel system.

The proposed solution integrates embedded vibration sensors with an internal damping mechanism, enabling real-time monitoring and attenuation of vibration directly at the cutting zone. A dynamic model of the machining system is developed to evaluate the influence of stiffness and damping on vibration amplitude. The results demonstrate that increasing the effective damping coefficient significantly reduces chatter intensity and enhances process stability.

The implementation of the hybrid smart-damped mandrel is expected to improve surface quality, extend tool life, and increase overall machining efficiency. This research contributes to the advancement of intelligent machining systems and provides a practical framework for vibration control in modern gear manufacturing.

Keywords: workgear, hob, hobbing process, modelling, cutting parameters

Analysis of Mounting Errors in Gear Hobbing

Mounting errors in gear hobbing processes represent a critical source of inaccuracy that directly affects the geometric quality of machined gears. These errors primarily arise from improper positioning of the gear blank on the mandrel, leading to deviations such as radial runout, axial misalignment, and non-uniform clamping. Radial runout occurs when the rotational axis of the workpiece does not coincide with the spindle axis, resulting in uneven tooth thickness and pitch variations. Axial misalignment, on the other hand, introduces lead errors and affects the longitudinal accuracy of gear teeth. Additionally, excessive or uneven clamping forces may cause elastic deformation of the gear blank, particularly in thin-walled components, further degrading dimensional precision. The cumulative effect of these mounting inaccuracies leads to increased vibration during cutting, reduced surface quality, and potential rejection of finished parts. Therefore, a detailed analysis of mounting errors is essential for improving the overall stability and accuracy of the gear hobbing process.

Radial Runout

Radial runout is one of the most critical mounting errors in gear hobbing processes, significantly influencing the dimensional accuracy and functional performance of machined gears. It occurs when the rotational axis of the gear blank does not coincide with the spindle axis, resulting in eccentric rotation during machining. This misalignment causes the cutting tool to engage the workpiece at varying radial distances throughout each revolution, leading to non-uniform material removal.

The magnitude of radial runout can be quantified using the following expression:

$$\Delta r = (D_{max} - D_{min}) / 2$$

where denote the maximum and minimum measured diameters of the rotating gear blank, respectively, typically obtained using a dial indicator.

From a kinematic perspective, radial runout introduces periodic variation in the effective cutting radius, which directly affects the geometry of the generated gear teeth. As a consequence, deviations in tooth thickness and pitch errors occur, leading to reduced meshing accuracy and increased transmission noise in gear operation. Furthermore, the eccentric motion generates cyclic fluctuations in cutting forces, which may induce vibration and contribute to the onset of chatter, particularly at higher spindle speeds.

The impact of radial runout becomes more pronounced in high-precision gear manufacturing, where tolerance limits are extremely narrow. Even small eccentricities can result in cumulative errors across multiple teeth, ultimately leading to rejection of the finished component. Additionally, radial runout may accelerate tool wear due to uneven load distribution on the cutting edges, thereby reducing tool life and increasing production costs.

To minimize radial runout, it is essential to ensure precise centering of the gear blank during installation. This can be achieved through the use of high-precision mandrels, self-centering mechanisms, and careful alignment procedures. The incorporation of improved mandrel designs with uniform contact surfaces and controlled clamping forces further enhances positioning accuracy and reduces eccentricity.

In summary, radial runout is a key factor affecting gear quality in hobbing processes, and its reduction is essential for achieving high machining accuracy, improved surface finish, and stable cutting conditions.

2.2 Axial Misalignment

Axial misalignment is a significant source of mounting error in gear hobbing processes, arising from improper positioning of the gear blank along the spindle axis. Such errors may occur due to inaccuracies in locating surfaces, improper seating on the mandrel, or uneven clamping conditions. As a result, the actual axial position of the workpiece deviates from its nominal location.

This type of misalignment directly affects the accuracy of the generated gear teeth, particularly influencing the tooth profile and lead. Axial deviations cause variations along the face width of the gear, leading to lead errors and non-uniform tooth geometry. Consequently, the contact pattern between meshing gears becomes irregular, which can result in increased noise, vibration, and localized stress concentrations during operation.

The magnitude of axial misalignment can be expressed as:

$$\Delta a = |L_{actual} - L_{nominal}|$$

where L_{actual} is the measured axial position of the gear blank, and $L_{nominal}$ is the intended design position.

Furthermore, axial misalignment affects the cutting kinematics by altering the relative position between the hob cutter and the workpiece. This is particularly critical in the machining of helical gears, where axial positioning is closely related to the accuracy of the helix angle. Even minor axial deviations can lead to cumulative geometric errors, reducing overall gear quality.

To minimize axial misalignment, it is essential to ensure precise axial positioning through the use of calibrated stops, precision spacers, and improved mandrel designs. Proper surface preparation and uniform clamping also play a key role in achieving stable and repeatable positioning.

In summary, axial misalignment is a critical factor affecting gear accuracy in hobbing processes, and its control is essential for ensuring high-quality gear production.

2.3 Clamping Deformation

Clamping deformation an important source of mounting error in gear hobbing processes, particularly when machining thin-walled or low-rigidity gear blanks. It occurs due to excessive or uneven distribution of clamping forces applied during the fixation of the workpiece on the mandrel or fixture system. When the clamping force exceeds the elastic limit of the material or is applied non-uniformly, elastic and sometimes plastic deformation of the gear blank may occur.

Such deformation leads to deviations in the original geometry of the workpiece, affecting both radial and axial accuracy. As a result, the gear tooth profile generated during hobbing deviates from its intended design, leading to errors in tooth thickness, pitch, and surface integrity. Moreover, clamping-induced deformation may relax during machining, causing time-dependent dimensional instability and additional vibration during cutting.

The magnitude of clamping deformation depends on several factors, including material properties, workpiece geometry, and the magnitude and distribution of clamping forces. It can be generally expressed as:

$$\Delta c \propto F_c / (E \cdot A)$$

where F_c is the clamping force, E is the modulus of elasticity of the workpiece material, and A is the effective contact area.

To minimize clamping deformation, it is essential to optimize clamping force distribution and use fixtures that ensure uniform load application. The use of precision mandrels with improved contact geometry, as well as soft jaw systems or adaptive clamping mechanisms, can significantly reduce deformation effects.

In conclusion, clamping deformation plays a critical role in determining the dimensional stability of gear blanks during hobbing and must be carefully controlled to ensure high machining accuracy and repeatability.

3. Theoretical Modeling of Positioning Accuracy

The overall positioning accuracy of the gear blank in gear hobbing processes is determined by the cumulative effect of individual mounting errors. These include radial runout, axial misalignment, and clamping deformation.

The total positioning error can be expressed as:

$$\Delta total = \sqrt{(\Delta r^2 + \Delta a^2 + \Delta c^2)}$$

where:

Δr — radial error,
Δa — axial misalignment,
Δc — clamping deformation.

This expression indicates that the total positioning error is governed by the root-sum-square contribution of individual error components, reflecting their combined influence on the overall mounting accuracy.

Furthermore, the relationship between positioning error and gear quality can be approximated as:

$$Eg \propto \Delta total$$


where Eg represents the resulting gear error, including deviations in tooth geometry, pitch accuracy, and surface quality.

This relationship demonstrates that an increase in mounting inaccuracies directly leads to deterioration in gear quality. Therefore, minimizing each individual error component is essential to achieving high-precision gear manufacturing.

4. Self-Centering Mandrel

The self-centering mandrel represents an advanced solution for improving the installation accuracy of gear blanks in gear hobbing processes. Its design is based on the use of precision tapered or conical locating surfaces, which ensure automatic alignment of the workpiece with the spindle axis during mounting. When the gear blank is positioned onto the mandrel, the conical interface generates a radial centering effect, minimizing eccentricity without requiring complex adjustment procedures. In addition, axial positioning is typically controlled by a calibrated stop surface, ensuring consistent and repeatable placement along the spindle axis. The clamping force is applied through a nut or drawbolt mechanism, which secures the workpiece while maintaining alignment.

From a mechanical standpoint, the self-centering effect reduces radial runout and improves concentricity, which directly enhances gear tooth accuracy and pitch precision. Compared to conventional rigid mandrels, this design offers improved repeatability and reduced setup time, making it particularly suitable for batch and mass production environments. However, the effectiveness of self-centering mandrels depends on the precision of the tapered surfaces and the quality of contact between mating components. Any wear, contamination, or manufacturing deviation in the taper geometry may lead to residual alignment errors. Despite these limitations, the self-centering mandrel remains a widely used and practical solution for achieving high positioning accuracy in gear hobbing operations.



References

1. Thomas Denkena, "Gear Manufacturing by Hobbing," *Production Engineering*, vol. 6, no. 1, pp. 55–62, 2012.
2. J. Peters, "Workpiece Clamping and Its Effect on Dimensional Accuracy," *Journal of Materials Processing Technology*, 2005.
3. E. Budak, "Analytical Prediction of Stability Lobes in Milling," *CIRP Annals*, 1995.
4. ISO 1328-1 — Cylindrical gears — ISO system of accuracy